



PROOF TESTED SINCE 1984
www.tandemloc.com
 Call Toll-Free: 1-800-258-7324
info@tandemloc.com

For extended information, specifications and drawings, visit
www.tandemloc.com/0_lifting/L_AN30-Coil-Hook.asp

**AN30A SERIES of COIL HOOKS
 BUY FACTORY-DIRECT**

COIL HOOK LIFTERS

This Below the Hook Lifter is used to lift coils, typically steel, aluminum and other materials.



1/2 Ton to 5 Ton Capacities in Stock

Tandemloc C-Hooks are designed for moving and positioning heavy coils with an overhead lifting device.

Narrow, space-saving profile.

Lead-in taper for easy insertion into coils.

Large, super-duty guide handles ease coil positioning and are designed for a lifetime of rugged service.

Please scroll down for detailed information on each style.

We can build custom coil hooks too. For pricing on a stock or custom coil hook, please contact the Tandemloc Sales Department.



- Does not require maintenance
- Simple, high strength design, low weight, high capability lifter
- Will hang level when loaded
- Load should be centered below hook lift location
- Integrated maneuvering handle for unloaded positioning of lifter
- Features edge protecting chamfers on lift arm
- **Proof Tested to 125% of WLL, Certification Provided**
- **Fully ASME B30.20 compliant**
- Stock item, usually ships within 1 business day

| MODEL | Working Load Limit (lbs.) | COIL DIMENSIONS | | | Unit Weight (lbs.) |
|----------------|---------------------------|---------------------|------------------|-------------------------|--------------------|
| | | Max. Diameter (in.) | Max. Width (in.) | Min. Eye Diameter (in.) | |
| AN30A01-08A-PA | 1,000 | 30 | 8 | 2.25 | 15 |
| AN30A01-12A-PA | 1,000 | 30 | 12 | 2.25 | 17 |
| AN30A02-08A-PA | 2,000 | 36 | 8 | 2.25 | 16 |
| AN30A02-16A-PA | 2,000 | 36 | 16 | 2.50 | 23 |
| AN30A04-08A-PA | 4,000 | 40 | 8 | 2.25 | 28 |
| AN30A04-16A-PA | 4,000 | 41 | 16 | 3.00 | 54 |
| AN30A07-12A-PA | 7,000 | 45 | 12 | 3.00 | 54 |
| AN30A07-16A-PA | 7,000 | 45 | 16 | 3.00 | 59 |
| AN30A07-20A-PA | 7,000 | 45 | 20 | 3.50 | 73 |
| AN30A10-16A-PA | 10,000 | 53 | 16 | 3.50 | 95 |
| AN30A10-20A-PA | 10,000 | 53 | 20 | 4.00 | 114 |

Coil dimensions approximate and are maximum limits.
 Lifter capacity is limited to capacity rating

