

TOP APERTURE PLATE MACHINED (T10021A-100)

Cage Code: 65059 | Drawing No: S9202 | Revision: A | Sheet: 1 of 1

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES





SECTION **A-A**

NOTES:
1. P/N: T10021A-100 TOP APERTURE PLATE MACHINED
2. TWISTLOC PULL OUT FORCE MEETS ISO 1161 LOAD RATINGS WHERE APPLICABLE
3. MATERIAL: LOW CARBON STEEL SUITABLE FOR WELDING
4. FINISH: SELF COLORED

To avoid lifter failure, potential death and property damage, never exceed WLL (Working Load Limit).

This document contains the proprietary information of Tandemloc, Inc. and your access and use shall be, and is at all times, pursuant to and limited by the Tandemloc, Inc. Terms of Use.

You shall not , and shall not encourage, assist, or authorize another party to copy, distribute, publicly display, modify, reverse engineer, decompile, or take any other action to reproduce this document or the information contained herein. © Copyright 2014 by Tandemloc, Inc.

Dimensions are subject to manufacturing tolerance and change.

TANDEMLOC INC

Email: info@tandemloc.com • www.tandemloc.com
824 Highway 101 • Havelock, NC 28532
Tel: 1.800.258.7324 (252.447.7155)
FAX 1.800.892.3273 (252.447.5502)

Tandemloc, Inc. designs, manufactures and tests lifting, securing and mobilizing components for all industries. See our website for details and important safety information.

Read all safety labels and instructions prior to use. Product to be used by qualified personnel only.