


This document contains the proprietary information of Tandemloc, Inc. and your access and use shall be, and is at all times, pursuant to and limited by the Tandemloc, Inc. Terms of Use. You shall not, and shall not encourage, assist, or authorize another party to copy, distribute, publicly display, modify, reverse engineer, decompile, or take any other action to reproduce this document or the information contained herein.

©2019 by Tandemloc, Inc.
Dimensions are subject to manufacturing tolerance and change.



- NOTES:
- PART NO.: AT14A070-480-PA, 276"-480" TELESCOPIC SPREADER
AT14A070-480SPA, 276"-480" TELESCOPIC SPREADER WITH TOP SLING
 - WLL: 70,000 LB. @ 45° MINIMUM
 - PROOF TESTED TO 125% (87,500 LB.) AND CERTIFIED
 - STANDARD SPECIFICATION # EAD21000A APPLIES
 - FINISH: SANDBLAST AND PRIME AND PAINT YELLOW
 - CALCULATED WEIGHT: 2,270 LB. SPREADER WITH SLING; 2,837 LB.
 - DESIGNED AND MANUFACTURED TO MEET OR EXCEED ASME B30.20 AND BTH-1, DESIGN CATEGORY B, SERVICE CLASS 0.

** DO NOT SIGN IF CHANGES ARE REQUIRED **

CUSTOMER APPROVAL: _____
DATE: _____

<small>1 1/2" DIMENSIONS APPLICABLE UNLESS OTHERWISE NOTED. DIMENSIONS ARE IN INCHES & TOLERANCES ARE: - XX ±.00, XXXX ±.000 - .XX ±.01</small>	<small>1" DIMENSIONS APPLICABLE UNLESS MAX. CLOSING TEL. IS: 0 TO 4" ±.03, 4.01" TO 7" ±.027 7.01" TO 10.5" ±.042 OVER 10.5" ±.052</small>	TANDEMLOC	
		TITLE: AT14A070-480-PA 276"-480" TELESCOPIC SPREADER	
<small>THIS DOCUMENT CONTAINS ONLY THE INFORMATION OF THE PRODUCT. IT DOES NOT INCLUDE ALL OF THE INFORMATION NECESSARY TO MANUFACTURE OR OPERATE THE PRODUCT. FOR COMPLETE INFORMATION, REFER TO THE DRAWINGS AND SPECIFICATIONS OF TANDEMLOC, INC.</small>	APPROVAL: _____ DATE: 09-21-19	REV: 001 D 65059	P/N: SAT14A070-480-PA-1 SHEET 1 OF 1