## 90"-120" TELESCOPIC SPREADER ASSEMBLY, WLL 100,000 LB. (AC22TH04-120-PA)

Cage Code: 65059 | Drawing No: SAC22TH04-120-PA | Revision: - | Sheet: 1 of 1

UNLESS OTHERWISE SPECIFIED. DIMENSIONS ARE IN INCHES

SIGHT HOLE, TYP. EACH SIDE

SHOULD SEE INNER PIPE COLOR.

IF NOT, DO NOT PERFORM LIFT.

1. PART NO.: AC22TH04-120-PA, 90"-120" TELESCOPIC SPREADER ASSEMBLY KIT

AC25C-025040EH

**SOLD SEPARATE** 

TYP., 2 PLACES

- 2. WLL: 100.000 LB.
- 3. PROOF TESTED TO 125% (125,000 LB.) AND CERTIFIED
- 4. STANDARD SPECIFICATION # EAD21000A APPLIES
- 5. FINISH: SANDBLAST, PRIME AND PAINT SAFETY YELLOW
- 6. CALCULATED WEIGHT: 192 LB.

**INNER PIPE** 

7. DESIGNED AND MANUFACTURED TO MEET OR EXCEED ASME B30.20 AND BTH-1, DESIGN CATEGORY B, SERVICE CLASS 0.

## KIT INCLUDES:

- 1. ONE PIPE ADAPTER FOR OVER ONE END CAP
- 2. ONE OUTER PIPE
- 3. ONE INNER PIPE 4. ONE OUTER PIPE PIN
- 5. ONE ADJUSTMENT PIN

INDICATES INADEQUATE OVERLAP. **OUTER PIPE PIN OUTER PIPE** 6.00, TYP.

 $\bigcirc$ 

30.00 OF ADJUSTMENT PIPE ADAPTER

> 90.00 CENTER TO CENTER FULLY COMPRESSED 120.00 CENTER TO CENTER FULLY EXTENDED



To avoid lifter failure, potential death and property damage, never exceed WLL (Working Load Limit).

This document contains the proprietary information of Tandemloc, Inc. and your access and use shall be, and is at all times, pursuant to and limited by the Tandemloc, Inc. Terms of Use.

You shall not, and shall not encourage, assist, or authorize another party to copy, distribute, publicly display, modify, reverse engineer, decompile, or take any other action to reproduce this document or the information contained herein. © Copyright 2014 by Tandemloc, Inc.

**ADJUSTMENT PIN** 

Dimensions are subject to manufacturing tolerance and change.



Email: info@tandemloc.com • www.tandemloc.com 824 Highway 101 • Havelock, NC 28532

Tel: 1.800.258.7324 (252.447.7155) FAX 1.800.892.3273 (252.447.5502)

Tandemloc, Inc. designs, manufactures and tests lifting, securing and mobilizing components for all industries. See our website for details and important safety information.

Read all safety labels and instructions prior to use. Product to be used by qualified personnel only.